



AC 900 Wireless Dual Band Router Archer C20

Highlights

- Brand New Wi-Fi Standard The advanced 802.11ac Wi-Fi gets your home network revolutionized
- Fast Wireless Concurrent 2.4GHz 450Mbps and 5GHz 433Mbps dual band Wi-Fi connections
- 3×3 MIMO at 2.4GHz Up to 50% speed up at 2.4GHz wireless band
- · Superior Coverage Three external antennas provide superior coverage
- Advanced Functions Manage your router cleverly with Parental Control and Guest Network functions
- · Tether App Provides easy router management in your palm



450Mbps+ Dual Band 433Mbps 2.4 & 5 GHz



Maximum



Guest Network



Parental Control



TP-LINK Tether App

Features



Speed

- Fast Wireless Speed Combined wireless speeds up to 883Mbps at 2.4GHz & 5GHz bands concurrently
- 3×3 MIMO Up to 50% speed up at 2.4GHz wireless band than standard AC routers
- 802.11ac Wi-Fi Standard The 5GHz wireless band offers 3 times faster data rate than wireless N in a single stream



Wi-Fi Range

- Three Antennas Three external antennas provide superior coverage
- High Gain High gain external antennas enhance Wi-Fi range and stability



Reliability

- Simultaneous Dual Band Reduces interference for more stable connections
- · IP QoS Advanced QoS automatically recognizes and prioritizes streaming & gaming applications

Features



Ease of Use

- One Button Connectivity Setup wireless connections safely and easily at a push of the WPS button
- Easy On/Off Dedicated Wi-Fi button allows users to turn wireless radio on or off
- Powerful Phone App Tether App provides an easy way to manage network setting on your palm
- · Intuitive Web UI Helps you set up the router in minutes



Security


- · Guest Network Allow guests to join your Wi-Fi network, while protecting your privacy
- Parental Control Establish restricted access policies for all connected devices
- Encryptions for Secure Network -WPA-PSK/WPA2-PSK encryptions provide active defense against security threats for user networks

Specifications

Hardware

- Ethernet Ports: 4 10/100Mbps LAN Ports & 1 10/100Mbps WAN Port
- · Button: WPS/Wi-Fi Button, Reset Button, Power On/Off Button
- External Power Supply: 9V/0.85A(EU), 12V/1A(US)
- Dimensions (W \times D \times H): 9.1 \times 5.7 \times 1.4 in (230 \times 144 \times 35mm)
- Antenna: 2 × 2.4GHz Antennas

1 × 5GHz & 2.4GHz Dual Band Antenna



Wireless

- · Wireless Standards: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
- Frequency: 2.4GHz and 5GHz
- · Signal Rate: 450Mbps at 2.4GHz, 433Mbps at 5GHz
- Transmit Power: CE: <20dBm(2.4GHz), <23dBm(5GHz)
- Reception Sensitivity: 5GHz: 11a 54M: -76dBm; 11ac VHT20 MCS8: -70dBm;

11ac VHT40 MCS9: -65.5dBm; 11ac VHT80 MCS9:

-61.5dBm

2.4GHz: 11g 54M: -76dBm11n; HT20 MCS7: -74dBm;

11n HT40 MCS7: -71dBm

- Wireless Function: Enable/Disable Wireless Radio, WDS Bridge, WMM,
 Wireless Statistics
- Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA-PSK2 encryptions
- \cdot 3 \times 3 MIMO: 450Mbps at 2.4GHz



Specifications

Software

- WAN Type: Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)/Bigpond
- · DHCP: Server, Client, DHCP Client List, Address Reservation
- · Quality of Service: WMM, Bandwidth Control
- · Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
- · Dynamic DNS: DynDns, Comexe, NO-IP
- · VPN Passthrough: PPTP, L2TP, IPSec
- Access Control: Parental Control, Local Management Control, Host list, Access Schedule, Rule Management
- Firewall Security: DoS, SPI Firewall, IP Address Filter/Domain Filter, IP and MAC Address Binding
- Protocols: Supports IPv4 and IPv6
- · Management: Access Control, Local Management, Remote Management
- Guest Network: 2.4GHz guest network, 5GHz guest network

Others

Package Contents

- · AC900 Wireless Dual Band Router Archer C20
- · Power Adapter
- · RJ45 Ethernet Cable
- · Quick Installation Guide

Certification

· CE, RoHS

System Requirements


- · Microsoft Windows XP/Vista/7/8/8.1/10, MAC OS, UNIX or Linux
- · Internet Explorer, Firefox, Chrome, Safari or other Java-enabled browsers
- · Cable or DSL or Fiber Modem/Terminal
- · Subscription with an Internet Service Provider (for Internet access)


Environment

- · Operating Temperature: 0°C ~40°C (32°F ~104°F)
- Storage Temperature: $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ ($-40^{\circ}\text{F} \sim 158^{\circ}\text{F}$)
- · Operating Humidity: 10%~90% non-condensing
- · Storage Humidity: 5%~90% non-condensing

Others

Ideal to use with





Similar Products











For more information, please visit

http://www.tplink.com/en/products/details/cat-9_Archer-C20.html

or scan the QR code left

Specifications are subject to change without notice. TP-LINK is a registered trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK Technologies CO., Ltd.

Maximum wireless speed of up to 883Mbps is the theoretical data rate derived from IEEE standard 802.11 specifications. Actual data throughput and wireless coverage will vary due to network conditions and environmental factors including volume of network traffic, building materials and construction, network overhead, actual data throughput rate, and wireless coverage. TP-LINK makes no express or implied representations or warranties about this product's compatibility with any future standards.

www.tp-link.com